D. No. 50-96-4/1, Floor II & III Srigowri Nilayam, Seethammadhara NE Visakhapatnam -530013

CIN: U51420MH2008PLC187689

Tel: +91 891 2858200 Fax: +91 891 2700864

www.seml.co.in



29-03-17

Ref. No: SMAL/EHS/REC/07

To
The Additional Principal chief conservator of Forest,
Ministry of Environment Forest and Climate Change,
Regional Office (SEZ),
Ist and IInd floor, Handloom Export Promotion Council,
34, Cathedral Garden Road, Nungambakkam,
Chennai – 34

Sub: Submission of Half yearly Compliance report of Environment Clearance- Reg

Ref: Environmental clearance Letter No. F.No. J11011/164/2009 IA.II (I) Dt. 26.11.2009 & subsequent amendment dt 04.05.2010

Dear sir,

Please find enclosed herewith our 12^h Half Yearly compliance report as per the stipulated condition imposed in Environment Clearance (EC). We are also enclosing herewith Environment Monitoring Analysis report as per the condition no.,XIV imposed in EC.

Thanking you with regards.

Yours truly

For Sarda Metals & Alloys Ltd.

Lajendra Volnz

Authorized Signatory

Copy to:

- The Regional Officer, Andhra Pradesh Pollution Control Board, Flat No.11, Shivaji colony, Pradeep Nagar, Vizianagram, A.P
- The Member Secretary, Andhra Pradesh Pollution Control Board, Paryavaran Bhavan, A-3, Industrial Estate, Sanath Nagar, Hyderabad- 500018, Andhra Pradesh

Compliances for the Conditions Imposed as Per Environmental Clearance Issued by MoEF Letter no.- F. No. J-11011/164/2009-IA.II(I), Dt. 26.11.2009 and subsequent amendment on Dt. 04.05.2010 for M/s. Sarda Metals & Alloys Ltd., APIIC Industrial Area, At village- Kantakapalli, Mandal- Kothavalasa, Dist.- Vizianagaram, Andhra Pradesh.

A. SPECIFIC CONDITIONS

S.		
No.	Conditions	Compliance
1	Efforts shall be made to reduce RSPM levels in the ambient air and a time bound action plan shall be submitted. On-line ambient air quality monitoring and continuous stack monitoring facilities for all the stacks and sufficient air pollution control devices viz. Electrostatic precipitator (ESP), gas cleaning plant, multi-cyclone, bag filter, de-duster etc. shall be provided to keep the emission levels below 100 mg/Nm³. At no time, the emission level shall go beyond the prescribed standards. Interlocking facilities shall be provided so that process can be automatically stopped in case emission level exceeds the limit. Analysis reports shall be submitted to the Ministry's Regional Office at Bangalore, CPCB and APPCB.	controlled systems like ESP, Bag house, Dust extraction system, & dust suppression system to maintain ambient air quality. On line ambient air quality monitoring and stack monitoring are installed and connected to APPCB. Interlocking facilities has been provided for automatic shut down of the system in
2	Hot gases from DRI kiln shall be passed through Dust Settling Chamber (DSC) to remove coarse solids and After Burning Chamber (ABC) to burn CO completely and used in waste heat recovery boiler (WHRB). The gas then shall be cleaned in ESP before leaving out into the atmosphere through ID fan and stack. Electrostatic precipitator (ESP) shall be provided to DRI plant, WHRB and ABC boilers to control air emissions within 100 mg/Nm ³ .	
3	Electro static precipitator (ESP) to sinter plant; ESP/multi-cyclone bag filter, de-duster to pellet plant; ESP and bag filter to power plant and DRI plant shall be provided to control air emissions within 100 mg/Nm³. Bag filter and de-duster to coke oven plant; dust extraction system with bag filters to blast furnace stock house, ferro alloys plant and ladle furnace; gas cleaning plant and bag filter to blast furnace; fume extraction system with cyclone to Induction furnace and heat recuperator shall be provided to rolling mill. The flue gas from rolling mill shall be discharged into the atmosphere through stacks of adequate height. Stacks of adequate height shall also be provided to all the concerned plants for effective dispersion of emissions into the atmosphere.	house for ferro alloys plant to control air emissions within 100 mg/Nm ³ . Provided adequate height of 120mts for CPP 80MW stack and 65mts for 2x33 MVA Ferro Furnace stack

Rayondie Volus

4	proposed coke oven plant as per the commitment submitted.	Presently not applicable; however shall be complied whenever required.
5	vide notification no. GSR 46 (E) dated 3 rd February, 2006 shall be followed as per the latest guidelines. Proper and full utilization of coke oven gases in power plant using waste heat recovery steam generators shall be ensured and no flue gases shall be discharged into the air.	Will be complied as per standards, whenever required.
6	Ministry and regularly monitored. Guidelines / Code of Practice issued by the CPCB shall be followed. The emission standards issued by the Ministry in May, 2008 for the sponge plants shall be followed.	per CPCB guidelines. An enclosed coal shed provided and close plantation done to control secondary emissions from coal stock pile. Presently not applicable however the emission standard for sponge plant will be followed whenever required.
7	material and finished product shall be controlled. Proper arrangements shall also be made to control dust emissions during loading and unloading of the raw material and finished product.	Only validity P.U.C certificate vehicles are allowed inside the plant premises. Dust suppression system provided during loading and unloading of raw material and finished product
8	In-plant control measures for checking fugitive emissions from all the vulnerable sources shall be provided. Dust suppression system with spray nozzles shall be provided to raw material handling area and material transfer points. Cyclones, bag filters, venturi scrubber shall be provided to transfer points to control fugitive emissions. Fume extraction and dry de-dusting system with bag filters shall be provided at the screening stations of ore, coke and other raw material handling areas to control fugitive emissions. Dust suppression system shall be provided in unloading areas. All internal roads shall be asphalted to prevent the fugitive dust emissions. Further, specific measures like water sprinkling around the stockpiles shall be done to control fugitive emissions.	are provided at transfer points Furthermore to control fugitive dus emissions of internal roads, continuous water sprinkler systems are being used.
9	Total water requirement from Tatipudi reservoir shall not exceed 396 m³/hr. No ground water shall be used. Air cooled condenser shall be provided to reduce the water consumption. Acidic and Alkaline effluent from DM water plant shall be neutralized and reused in the plant through ash pond. All the effluent shall be treated and recycled in the re-circulating system or used for ash handling, dust suppression and green belt development.	Water required from Tatipudi reservoir is being maintained within the stipulate limit of less than 396 m³/hr. No Groun water is being used. Provided Air coole condenser and neutralizing pit. To ensur zero effluent discharge, neutralized put water, cooling tower effluent an Domestic waste water being used for du

	All the wastewater from process and domestic sources shall be treated and recycled and reused. No wastewater shall be discharged outside the premises and Zero effluent discharge shall be ensured.	suppression & green belt development.
10	Prior permission for the drawl of 396 m ³ /hr water from Tatipudi reservoir from the concerned department shall be obtained and a copy of the permission letter shall be submitted to the Ministry and its Regional Office at Bangalore	KL/day is obtained from the Greater Visakhapatnam Municipal Corporation
11	The water consumption shall not exceed 16 m ³ /Ton of Steel as per prescribed standard.	Presently not applicable and will be followed whenever required.
12	Ground water monitoring around the solid waste disposal site / secured landfill (SLF) shall be carried out regularly and report submitted to the Ministry's Regional Office at Bangalore, CPCB and APPCB.	Test report is attached.
13	No coal fines shall be imported as proposed. DRI Fines, coke breeze, sinter dust, GCP dust, blast furnace dust, SMS dust, scale, iron ore fines shall be used in sinter plant. Scrap from rolling mill shall be used as raw material in SMS. Char/dolochar shall be used in power plant / brick manufacturing plants. Manganese slag from ferro alloy plant shall be used as raw material for Silico-Manganese production. All the other solid wastes including broken refractory mass shall be properly disposed off in environment-friendly manner. Oily waste shall be provided to authorized recyclers/reprocessors.	whenever required Manganese slag from ferro alloy plant is being used as a raw material for Silico-
14	AFBC Plant shall be installed before installation of sponge iron plant so that utilization of char in the AFBC boiler is ensured. All the char from DRI plant shall be utilized in AFBC boiler of power plant and no char shall be disposed off anywhere else. All the blast furnace (BF) slag shall be granulated and provided to cement manufacturers for further utilization. Sludge from STP shall be used as manure for green belt development.	
15	All type of slag shall be used for road making only after passing through Toxic Chemical Leachability Potential (TCLP) test. Otherwise, toxic waste shall be recovered from the slag and output waste shall be disposed in secured landfill as per CPCB guidelines. Spent oil shall be sold to APPCB authorized recyclers.	Being complied. Report is enclosed.

					,	
	16	Proper handling, storage, utilization and disposal of all the solid waste shall be ensured and regular report regarding toxic metal content in the waste material and its composition, end use of solid/hazardous waste shall be submitted to the Ministry's Regional Office at Bangalore, APPCB and CPCB.	manufac toxic me	ture. Tes	t report att	ached for
	17	A time bound action plan shall be submitted to reduce solid waste, its proper utilization and disposal.		aste is bei manufact		ed free of cost
		-	Fly a	sh generati	ion and utili	zation Data
			Fin. Yr	Ash Gen	Utilizatio	n of flyash (%)
				in Ton	Sold to bri manufactu	1
			2013-14	32662.08	4.1	95.9
		·	2014-15	22733.22	2.18	97.82
			2015 -16	21444.38	38.02	61.98
			2016-17	14654.49	83.4	16.59
		·	SiM	In slag Gen	and Utiliza	tion Data
			Fin. yr	SiMn gen		of SiMn (%)
. ,	-			in Ton	Sold to bric manufacture	1 13
			2014-15	18287.41	0	100
			2015-16	16466.01	94.46	Stock in hand
			2016-17	68335.23	72.51	Stock in hand
	18	2003. All the fly ash shall be provided to cement and	plan as p	complied er under:	. Fly ash u	tilization
		brick manufacturers for further utilization and Memorandum of Understanding shall be submitted to the Ministry's Regional Office at Bangalore.		Man	ufacture	In house land for reclamation
		the minimuy's regional Office at Bangaiore.	2015-201		38.02	61.98
			2016 - 20		65	35
	10		2017 – 20		100	-
		As proposed, green belt shall be developed in 92.72 acres (33 %) out of total 280.96 acres in and around the plant as per the CPCB guidelines in consultation with	Complie	d.		-

20	Proper rain water harvesting measures shall be adopted to make use of water within the plant premises for various activities including dust suppression and green belt development	within the site
21	All the environment management measures given in the EIA/EMP shall be implemented and complied with.	Complied.
22	All the recommendations made in the Charter on Corporate Responsibility for Environment Protection (CREP) for the Steel Sector including Coke Oven Plants shall be implemented.	required/applicable
23	Permission and recommendations of the State Forest Department regarding impact of proposed plant on Adanapalem RF shall be obtained regarding likely impact of the proposed steel plant on the surrounding reserve forest and recommendations, if any, shall be implemented.	Divisional Forest Officer, Vizianagaram & Principal Chief Conservator of Forests; it is concluded that there will be no
24	The company shall provide housing for construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, creche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.	structures were removed

GENERAL CONDITIONS

S No.	Conditions	Compliances
1	The project authorities shall strictly adhere to the stipulations made by the Andhra Pradesh Pollution Control Board (APPCB).	
2	At no time, the emissions shall exceed the prescribed limits. In the event of failure of any pollution control system adopted by the unit, the unit shall be immediately put out of operation and shall not be restarted until the desired efficiency has been achieved.	-

Rejende Volne

3	No further expansion or modifications in the plant shall be carried out without prior approval of the Ministry of Environment and Forests. In case of deviations or alterations in the project proposal from those submitted to this Ministry for clearance, a fresh reference shall be made to the Ministry to assess the adequacy of conditions imposed and to add additional environmental protection measures required, if any.	
4	The gaseous emissions from various process units shall conform to the load/mass based standards notified by this Ministry on 19 th May, 1993 and standards prescribed from time to time. The APPCB may specify more stringent standards for the relevant parameters keeping in view the nature of the industry and its size and location. At no time, the emission level shall go beyond the prescribed standards. Interlocking facilities shall be provided so that process can be automatically stopped in case emission level exceeds the limit.	APPCB. Interlocking facility is being provided for process to automatically
5	The project authorities shall strictly comply with the rules and regulations under Manufacture, Storage and Import of Hazardous Chemicals Rules, 1989 as amended in October, 1994 and January, 2000. Authorization from the APPCB shall be obtained for collection, treatment, storage, and disposal of hazardous wastes.	
6	The project authorities must strictly comply with the rules and regulations with regard to handling and disposal of hazardous wastes in accordance with the Hazardous Wastes (Management and Handling) Rules, 2003. Authorization from the A. P. Pollution Control Board must be obtained for collection / treatment / storage / disposal of hazardous wastes.	Being complied
7	The overall noise levels in and around the plant area shall be kept well within the standards (85 dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise levels shall conform to the standards prescribed under Environment (Protection) Act, 1986 Rules, 1989 viz. 75 dBA (day time) and 70 dBA (night time).	are measured Third party analysis
8	The company shall develop rain water harvesting structures to harvest the rain water for utilization in the lean season besides recharging the ground water table.	_

9	Occupational Health Surveillance of the workers shall be done on a regular basis and records maintained as per the Factories Act.	Occupational Health Surveillance of the workers is being done and records are maintained
10	A separate Environmental Management Cell equipped with full fledged laboratory facilities shall be set up to carry out the environmental management and monitoring functions.	Being complied
11	As proposed, Rs. 100.00 Crores and Rs. 5.00 Crores shall be earmarked towards capital cost and recurring cost/annum for environment pollution control measures shall be judiciously used to implement the conditions stipulated by the Ministry of Environment and Forests as well as the State Government. A time bound implementation schedule shall be submitted to the Ministry and its Regional Office at Bangalore to implement all the conditions stipulated herein. The funds so provided shall not be diverted for any other purpose.	
12	A copy of clearance letter shall be sent by the proponent to concerned Panchayat, Zilla Parishad / Municipal Corporation, Urban Local Body and the local NGO, if any, from whom suggestions / representations, if any, were received while processing the proposal. The clearance letter shall also be put on the web site of the company by the proponent.	website: www.seml.co.m
13	The project proponent shall upload the status of compliance of the stipulated environment clearance conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of the MOEF at Bangalore, the respective Zonal Office of CPCB and the APPCB. The criteria pollutant levels namely; SPM, RSPM, SO ₂ , NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the projects shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.	reports are enclosed.
14	The project proponent shall also submit six monthly reports on the status of the compliance of the stipulated environmental conditions including results of monitored data (both in hard copies as well as by email) to the Regional Office of MOEF, the respective Zonal Office of CPCB and the APPCB. The Regional Office of this Ministry at Bangalore / CPCB / APPCB shall monitor the stipulated conditions.	

Rojenda Volne

•			
	15	The environmental statement for each financial year ending 31 st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of	
		environmental conditions and shall also be sent to the respective Regional Offices of the MOEF by e-mail.	
	16	The Project Proponent shall inform the public that the project has been accorded environmental clearance by the Ministry and copies of the clearance letter are available with the APPCB and may also be seen at Website of the Ministry of Environment and Forests at http://envfor.nic.in. This shall be advertised within seven days from the date of issue of the clearance letter, at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular language of the locality concerned and a copy of the same should be forwarded to the Regional office.	Complied
	17	Project authorities shall inform the Regional Office as well as the Ministry, the date of financial closure and final approval of the project by the concerned authorities and the date of commencing the land development work.	term loans sanctioned by Bank/FI and

Rayerch Volre

TEAM

DUPLICATE

Form-No. TCL/L/GF/RF-138

Labs and Consultants

Registered Office:

2255

B-115, 116, 117 & 509, Annapoorna Block, Aditya Enclave, Ameerpet, Hyderabad - 530038. Ph.: (O) 040-23748555 / 23748616, Fax: 040-23748666, Email: teamlabs@gmail.com

ISO 9001 : 2008, ISO 14001 : 2004 and OHSAS 18001 : 2007 Certified Organization Laboratory Recognised by Ministry Environment, Forests and Climate Change, Gol, New Delhi

TEST REPORT

Test Report No.TLC/V/ENV/SMAL/ 01/0317

DT18.04.2017

Description of Test:

Ambient Noise Level Monitoring

Name of the client:

M/s Sarda Metals & Alloys Limited

Kothavalasa, Vizianagram

Location of Monitoring:

As per details Given

Date of monitoring:

11.04.2017

No	Location Noise leve		el dB(A)
		Day	Night
1	Near Main gate	67.4	60.9
2	Near DM Plant.	58.1	54.2
3	Near Project office	67.1	62.6
4	Near Boiler Area	70.2	68.0
5	Near Store area	61.8	55.6
6	Canteen area	68.4	61.6
7	Near CHP Area	62.5	59.1
. 8	Furnace-1 area	71.8	67.6
9	Furnace-2 area	72.1	68.4
:•	CPCB Standard for Ambient Noise Levels	75	70



Labs and Consultants

Registered Office:

B-115, 116, 117 & 509, Annapoorna Block, Aditya Enclave, Ameerpet, Hyderabad - 530038. Ph.: (O) 040-23748555 / 23748616, Fax: 040-23748666, Email: teamlabs@gmail.com ISO 9001 : 2008, ISO 14001 : 2004 and OHSAS 18001 : 2007 Certified Organization

Laboratory Recognised by Ministry Environment, Forests and Climate Change, Gol, New Delhi

TEST REPORT

Test Report No.TLC/V/ENV/SMAL/ 02/0317

DT18.04.2017

Description of Test:

Stack Emissions Analysis

Name of the client:

M/s Sarda Metals & Alloys Limited

Kothavalasa, Vizianagram

Location of sampling:

As per details given

Parameter	Stack attached to FID	Stack attached to CPP
Date of sampling/time	11.04.2017	17.03.2017
Stack height(m)	65	120
Stack diameter (m)	4.0	6.7
Stack area (m) ²	12.57	35.27
Flue gas temp ⁰ c	179	221
Exit gas velocity (m/s)	11.6	3.9
Flue gas flow rateNM ³ /hr	346078	298718
Emission Rates		
Dust concentration mg/NM ³	34	30
SO2 mg/NM ³		142
NOx mg/NM ³	-	125
Hg mg/NM ³	- :	<0.01

^{*}Test Method:IS11255

Labs and Consultants

Registered Office:

2257

B-115, 116, 117 & 509, Annapoorna Block, Aditya Enclave, Ameerpet, Hyderabad - 530038. Ph. : (O) 040-23748555 / 23748616, Fax : 040-23748666, Email : teamlabs@gmail.com

ISO 9001 : 2008, ISO 14001 : 2004 and OHSAS 18001 : 2007 Certified Organization Laboratory Recognised by Ministry Environment, Forests and Climate Change, Gol, New Delhi

TEST REPORT

Test Report No.TLC/V/ENV/SMAL/ 03/0317

DT18.04.2017

Description of Test:

Stack Emissions Analysis

Name of the client:

M/s Sarda Metals & Alloys Limited


Kothavalasa, Vizianagram

Location of sampling:

As per details given

Parameter	Stack attached to DGI 250KVA	Stack attached to DGII 250KVA	CPCB Standard g/kWh
Date of sampling/time	17.03.2017	17.03.2017	
Stack height(m)	10.0	10.0	
Stack diameter (m)	0.125	0.125	
Stack area (m) ²	0.0123	0.0123	
Flue gas temp ⁰ c	182	199	
Exit gas velocity (m/s)	16.8	18.65	
Flue gas flow rateNM ³ /hr	487	521	
Emission Rates			
Dust concentration g/kWh	0.171	0.197	0.3
CO g/kWh	0.584	0.417	3.5
NOx g/kWh	0.637	0.776	9.2
HC g/kWh	0.05	0.04	1.3

^{*}Test Method:IS11255



TEAM

Labs and Consultants

DUPLICATE

Form-No. TCL/L/GF/RF-138

2253

Registered Office:

B-115, 116, 117 & 509, Annapoorna Block, Aditya Enclave, Ameerpet, Hyderabad - 530038. Ph.: (O) 040-23748555 / 23748616, Fax: 040-23748666, Email: teamlabs@gmail.com

ISO 9001 : 2008, ISO 14001 : 2004 and OHSAS 18001 : 2007 Certified Organization Laboratory Recognised by Ministry Environment, Forests and Climate Change, Gol, New Delhi

TEST REPORT

Test Report No .TLC/V/ENV/SMAL/ 04/0317

DT18.04.2017

Description of test:

Ambient Air Quality Monitoring

Name of the Industry:

M/s Sarda Metals & Alloys Limited

Date of Sampling:

16.03.2017 to 17.03.2017

Location of industry:

APIIC, Sarda Industrial Park, Kantakapalli,

Kothavalasa, Vizianagram

S.No.	Location	PM ₁₀	PM _{2.5}	SO ₂	NO _X
1	Near Security Gate	68	39	10.2	18.2
2	Beside Conveyor belt	78	43	11.8	17.2
3	Near DM Plant	59	31	8.2	16.6
	Protocol	IS5182 PART- 23 -2006	Gravi metric, CPCB Manual page15-30	IS5182 PART-2 - 2001	IS5182 PART- 6 -2004
	APPCB STANDARD	100	60	80	80

2253

Labs and Consultants

Registered Office:

B-115, 116, 117 & 509, Annapoorna Block, Aditya Enclave, Ameerpet, Hyderabad - 530038. Ph.: (O) 040-23748555 / 23748616, Fax: 040-23748666, Email: teamlabs@gmail.com

ISO 9001 : 2008, ISO 14001 : 2004 and OHSAS 18001 : 2007 Certified Organization Laboratory Recognised by Ministry Environment, Forests and Climate Change, Gol, New Delhi

Test Report No .TLC/V/ENV/SMAL/ 01/0417 DT18.04.2017

Description of test:

Drinking Water Analysis

Name of the Industry:

M/s Sarda Metals & Alloys Limited

Date of Sampling:

11.04.2017

Location of industry:

APHC, Sarda Industrial Park, Kantakapalli,

Kothavalasa Vizianagram

	Kothavalasa, Vizianagram					
No	Parameter	Test method	Drinking water	Acceptable limit as per IS10500-2012		
1	Colour (Hazen Units)	IS:3025 Part 4- 1983	5	5 Max.		
2	Turbidity, NTU	IS:3025 Part 10-1984	1.8	1 Max.		
3	рН	IS:3025 Part 11-1983	6.80	6.5 to 8.5		
4	Total Dissolved Solids, mg/l	IS:3025 Part 16-1984	165	500 Max.		
5	Aluminium as Al, mg/l	SM 3125	0.02	0.03max		
6	Barium as Ba, mg/l	SM 3125	0.01	0.7max		
7	Chlorides as Cl, mg/l	IS:3025 Part 32-1988	28	250 Max.		
8	Copper as Cu, mg/l	SM 3125	<0.01	0.05 Max.		
9	Fluoride as F, mg/l	SM 4500 F- D	0.5	1.0 Max.		
10	Iron as Fe, mg/l	SM 3125	0.03	0.3 Max.		
11	Magnesium as Mg, mg/l	IS:3025 Part 46-1994	9.36	30 Max.		
12	Manganese as Mn, mg/l	SM 3125	0.01	0.1 Max.		
13	Sulphate as SO ₄ , mg/l	1S:3025 Part 24-1986	18	200 Max.		
14	Sulohide as H ₂ S, mg/l	IS 3025 (Part 29)	<0.01	0.005 max		
15	Total Alkalinity as calcium carbonates, mg/l	IS:3025 Part 23-1986	55	200 Max.		
16	Total Hardness as CaCO ₃ ,mg/l	IS:3025 Part 21-2009	110	200 Max.		
17	Zinc as Zn, mg/l	SM 3125	0.04	5 Max.		
18	Calcium as Ca, mg/l	IS:3025 Part 40-1991	28	75 max		
19	Nitrate as NO3, mg/l	SM 4500 NO3- B	5.2	45 max		
20	Cadmium, mg/L	SM 3125	<0.001	0.003		
21	Cyanide as CN, mg/L	SM 4500CN E	< 0.01	0.05		
22	Lead as Pb, mg/L	SM 3125	< 0.01	0.01		
23	Mercury as Hg, mg/L	EPA 200.8	< 0.001	0.001		
24	Nickel as Ni, mg/L	SM3125	<0.01	0.02		
25	Total Arsenic as As, mg/L	SM 3125	< 0.001	0.01		
26	Total Chromium as Cr, mg/L	SM 3125	<0.01	0.05		
27	Standard Plate Count at 37°C No of colonies/ml	IS 1622:1981	2	10		
28	Total Coliform Bacteria at 37°C MPN/100 ml	IS 1622:1981	Nil	Nil		

2267

Labs and Consultants

Registered Office:

B-115, 116, 117 & 509, Annapoorna Block, Aditya Enclave, Ameerpet, Hyderabad - 530038. Ph. : (O) 040-23748555 / 23748616, Fax : 040-23748666, Email : teamlabs@gmail.com

ISO 9001 : 2008, ISO 14001 : 2004 and OHSAS 18001 : 2007 Certified Organization Laboratory Recognised by Ministry Environment, Forests and Climate Change, Gol, New Delhi

TEST REPORT

Test Report No .TLC/V/ENV/SMAL/ 02/0417

DT18.04.2017

Description of test:

STP Waste Water Analysis

Name of the Industry:

M/s Sarda Metals & Alloys Limited

Date of Sampling:


11.04.2017

Location of industry:

APIIC, Sarda Industrial Park, Kantakapalli,

Kothavalasa, Vizianagram

S.No.	Parameter	STP Outlet	APPCB discharge standard	protocol
1	p ^H	7.6	6.5-8.5	IS:3025 Part 11-1983
2	TDS as mg/l	1260	2100	IS:3025 Part 16-1984
3	TSS as mg/l	65	100	IS:3025 Part 17-1984
4	BOD as mg/l	22	30	IS:3025 Part 44-1993
5	COD as mg/l	140	250	IS:3025 Part 58-2006
-6	Oil& Grease as mg/l	1.5	10.0	IS:3025 Part 39-1991



Labs and Consultants

Registered Office:

2261

B-115, 116, 117 & 509, Annapoorna Block, Aditya Enclave, Ameerpet, Hyderabad - 530038. Ph. : (O) 040-23748555 / 23748616, Fax : 040-23748666, Email : teamlabs@gmail.com

ISO 9001 : 2008, ISO 14001 : 2004 and OHSAS 18001 : 2007 Certified Organization Laboratory Recognised by Ministry Environment, Forests and Climate Change, Gol, New Delhi

TEST REPORT

Test Report No .TLC/V/ENV/SMAL/ 05/0317

DT18.04.2017

Description of test:

Water Analysis

Name of the Industry:

M/s Sarda Metals & Alloys Limited

Date of Sampling:

17.03.2017

Source of collection:

As per details given

Location of industry:

APIIC, Sarda Industrial Park, Kantakapalli,

Kothavalasa, Vizianagram

S.No.	Parameter	FAD Cooling Tower	CPP Cooling Tower	Neutralizat ion Pit	APPCB discharge standard	protocol
1	p ^H	8.2	6:9	8.05	6.5-8.5	IS:3025 Part 11-1983
2	TDS as mg/l	1287	1055	805	2100	IS:3025 Part 16-1984
3	TSS as mg/l	15	12	18	100	IS:3025 Part 17-1984
4	BOD as mg/l	6	5	5	30	IS:3025 Part 44-1993
5	COD as mg/l	85	72	68	250	IS:3025 Part 58-2006
6	Oil& Grease as mg/l	Nil	Nil	Nil	10.0	IS:3025 Part 39-1991





www.ctllabs.in www.foodenvironmenttesting.com

CIN: U74999TN2008PTC067568

TEST REPORT

Report Number and date	CTL/CH/M-0267/2017-18 & 26.04.2017					
Sample Number	M-0267/17-18					
Customer Name & Address	M/s. Sarda Metals & Alloys Ltd., D.No.50-96-4/1, Floor II & III, Srigowri Nilayam, Seethammadhara NE, Visakhapatnam - 530 013.					
	SAMPLE DETAILS					
Sample Description By Customer	Fly Ash					
Sampling Date	NA	Sampled By	Customer			
Sampling Location	NA	Sampling Method	NA			
Quantity Received	1 Kg Lot / Batch No Not Available					
Date of Receipt	13.04.2017 Sample Condition Good & Received in Packed Condition					
Analysis Starting Date	17.04.2017	Analysis Completion Date	25.04.2017			

Test Results:

The above sample tested as received, and results are as follows:

S. NO	PARAMETERS	METHOD	UNITS	RESULTS			
TCLP A	TCLP Analysis:						
1	Arsenic		mg/l	BDL(DL:0.01)			
2	Barium		mg/l	BDL(DL:0.5)			
3	Cadmium		mg/l	BDL(DL:0.05)			
4	Chromium		mg/l	BDL(DL:0.1)			
5	Lead		mg/l	BDL(DL:0.1)			
6	Mercury		mg/l	BDL(DL:0.01)			
7	Selenium		mg/l	BDL(DL:0.01)			
8	Silver		mg/l	BDL(DL:0.1)			
9	Manganese		mg/l	0.86			
10	Antimony	SW - 846 Methods 1311 TCLP	mg/l	BDL(DL:0.01)			
11	Hexavalent Chromium as Cr ⁶⁺		mg/l	BDL(DL:0.05)			
12	Cobalt		mg/l	BDL(DL:0.1)			
13	Copper		mg/l	0.09			
14	Molybdenum		mg/l	BDL(DL:0.1)			
15	Nickel		mg/l	0.21			
16	Zinc		mg/l	0.12			
17	Beryllium		mg/l	BDL(DL:0.1)			
18	Thallium		mg/l	BDL(DL:0.5)			
19	Vanadium		mg/l	BDL(DL:2.0)			

BDL - Below Detection Limit; DL - Detection Limit

Verified by

END OF REPORT

For Chennai Testing Laboratory Pvt ltd

A. Daymmy.

Authorised Signatory

Page 1 of 1



www.ctllabs.in www.foodenvironmenttesting.com

CIN: U74999TN2008PTC067568

TEST REPORT

Report Number and date	CTL/CH/M-0268/2017-18 & 26.04.2017					
Sample Number	M-0268/17-18					
Customer Name & Address	M/s. Sarda Metals & Alloys Ltd., D.No.50-96-4/1, Floor II & III, Srigowri Nilayam, Seethammadhara NE, Visakhapatnam - 530 013.					
	SAMPLE DETAILS					
Sample Description By Customer	Bag House Dust					
Sampling Date	NA	Sampled By	Customer			
Sampling Location	NA	Sampling Method	NA			
Quantity Received	d 1 Kg Lot / Batch No Not Available					
Date of Receipt	13.04.2017 Sample Condition Good & Received in Packed Condition					
Analysis Starting Date	17.04.2017	Analysis Completion Date	25.04.2017			

Test Results:

The above sample tested as received, and results are as follows:

S. NO	PARAMETERS	METHOD	UNITS	RESULTS				
TCLP A	TCLP Analysis:							
1	Arsenic		mg/l	BDL(DL:0.01)				
2	Barium		mg/l	BDL(DL:0.5)				
3	Cadmium		mg/l	BDL(DL:0.05)				
4	Chromium		mg/l	BDL(DL:0.1)				
5	Lead		mg/l	1.22				
6	Mercury		mg/l	BDL(DL:0.01)				
7	Selenium		mg/l	BDL(DL:0.01)				
8	Silver		mg/l	BDL(DL:0.1)				
9	Manganese		mg/l	7.3				
10	Antimony	SW - 846 Methods 1311 TCLP	mg/l	BDL(DL:0.01)				
11	Hexavalent Chromium as Cr ⁶⁺		mg/l	BDL(DL:0.05)				
12	Cobalt		mg/l	BDL(DL:0.1)				
13	Copper		mg/l	0.09				
14	Molybdenum		mg/l	BDL(DL:0.1)				
15	Nickel		mg/l	0.16				
16	Zinc		mg/l	48.2				
17	Beryllium		mg/l	BDL(DL:0.1)				
18	Thallium		mg/l	BDL(DL:0.5)				
19	Vanadium		mg/l	BDL(DL:2.0)				

BDL - Below Detection Limit; DL - Detection Limit

N.D.L. Verified by

END OF REPORT

For Chennai Testing Laboratory Pvt ltd

A. Dayumy.

Authorised Signatory

Page 1 of 1



www.ctllabs.in www.foodenvironmenttesting.com

CIN: U74999TN2008PTC067568

TEST REPORT

Report Number and date	CTL/CH/M-0269/2017-18 & 26.04.2017					
Sample Number	M-0269/17-18					
Customer Name & Address	M/s. Sarda Metals & Alloys Ltd., D.No.50-96-4/1, Floor II & III, Srigowri Nilayam, Seethammadhara NE, Visakhapatnam - 530 013.					
SAMPLE DETAILS						
Sample Description By Customer	Silico Manganese Slag					
Sampling Date	NA	Sampled By	Customer			
Sampling Location	NA	Sampling Method	NA			
Quantity Received	Quantity Received 1 Kg Lot / Batch No Not Available					
Date of Receipt	13.04.2017 Sample Condition Good & Received in Packed Condition					
Analysis Starting Date	17.04.2017	Analysis Completion Date	25.04.2017			

Test Results:

S. NO	PARAMETERS	METHOD	UNITS	RESULTS				
TCLP A	TCLP Analysis:							
1	Arsenic		mg/l	BDL(DL:0.01)				
2	Barium		mg/l	BDL(DL:0.5)				
3	Cadmium		mg/l	BDL(DL:0.05)				
4	Chromium		mg/l	BDL(DL:0.1)				
5	Lead		mg/l	BDL(DL:0.1)				
6	Mercury		mg/l	BDL(DL:0.01)				
7	Selenium		mg/l	BDL(DL:0.01)				
8	Silver		mg/l	BDL(DL:0.1)				
9	Manganese		mg/l	6.7				
10	Antimony	SW - 846 Methods 1311 TCLP	mg/l	BDL(DL:0.01)				
11	Hexavalent Chromium as Cr ⁶⁺		mg/l	BDL(DL:0.05)				
12	Cobalt		mg/l	BDL(DL:0.1)				
13	Copper		mg/l	0.05				
14	Molybdenum		mg/l	BDL(DL:0.1)				
15	Nickel		mg/l	0.14				
16	Zinc		mg/l	0.26				
17	Beryllium		mg/l	BDL(DL:0.1)				
18	Thallium		mg/l	BDL(DL:0.5)				
19	Vanadium		mg/l	BDL(DL:2.0)				

BDL - Below Detection Limit; DL - Detection Limit

Verified by

END OF REPORT

For Chennai Testing Laboratory Pvt ltd

A. Dayumy

Authorised Signatory

Page 1 of 1